

P3.91 Outdoor Display

K Series

CH-OMP

I L L U M I N A T E Y O U R W O R L D



P3.91 Outdoor Display

K Series

Die-casting Aluminum strong rigid, not easy to de orm, more accurate splicing

500×500/500×1000×86mm











RGB

Adjustable Radian

Seamless Splicing







Fast Maintenance

HD Display

Saving Energy







Quiet

Wide Angle Display

IP65





Rubber Handle Fast Lock (Curved Lock Available) Brand Logo **Indicator Light Control Box**

Positioning Pin

Anti-collision Corner

Truss Quick Connection Hole

Led Module

Rubber Handle

LED Module Protection

Positioning Beads





Ultra thin, thickness only 86 mm





Light Weight

500*500mmcanbinet only 8 kg 500*1000mmcanbinet only 14.8 kg






Die-casting Aluminum Cabinet

Strong rigidity, no deformation, more accurate splicing, ergonomic structural design, easyinstallation by one person.







Truss Connection Lock Hole

Supporting the truss connecting rental cabinet quickly, as well as the hoisting and fixed installation of the truss.





Arc Lock Design

Multiple models, can be extended various shapes to meet the needs of special scenes.

* Arc lock is an optional function




Anti-collision Corner

Effectively protecting the led lamp of the corner led modules from colliding and falling off during transportation or repeated disassembly when for rental.

**Anti-collision Corner is an optional function







Precise Positioning Of Installation

Seamless splicing between the upper and lower, left and right positions of the quick docking cabinet to improve the installation efficiency.







LED Module Protection

Keep a gap between the bottom LED modules and ground to avoid collided when transporting.








Ultra-wide Viewing Angle

super wide viewing angle, deducing the same wonderful effect from different angles 160°



16-bit Higher Grey Level



Grey level is the decisive factor for displaying the colors.
The higher the Grey level, the richer the displayed colors and the more delicate the picture.



3840Hz High Refresh Rate





Low refresh rate

High refresh rate

The display is smooth like flowing water, the picture quality is clear, and the colors are bright and distinct.



Ultra High Definition




To guarantee the premium visual effect with higher deinition, higher contrast, and higher saturation.





Using High-quality Lamp Beads

Longer life than general products on the market.









Unit:mm



型 号 Type Number	CH-IMP3.9	CH-IMP3.9X	CH-OMP3.9	CH-OMP3.9X
规格尺寸 Dimension(MM)	500x 500x 86MM	500x1000x86MM	500 x 500x 86MM	500x1000x86MM
最大功率Max.Power(W)	100W	200W	300W	600W
箱体重量 Cabinet Weight(KG)	8KG	14.5KG	8KG	14.8KG
亮度Brightness(CD/m)	≥600CD/m²		≥ 7000 CD/M2	
LED规格 LED Standard	SMD2020		SMD1921	
可视角度 Viewing Angle	120°		160°	
防护等级 Protection Level	P42		IP65	
刷新率 Refresh Rate(Hz)	1920Hz/3840Hz			
像素点间距 Pixel Pitch(MM)	3.91MM			
扫描模式 Scan Mode	1/16 Scan			
像素密度 Pixel Density(Dot/m)	65536 Dot/m²			
箱体材质 Cabinet Material	Aluminum Alloy			
维护方式 Maintenance Method	Back Maintenance			
灰度等级 Grey Level	16 Bit			
工作温度Working Temperature	-20~60°C			
工作湿度Working Humidity	10%-90%RH			
使用寿命 Life Span	≥50000 Hours			
工作电压 Working Voltage	AC 110V/220V,50/60HZ			



CERTIFICATE





CARGO SHIPPING

Frequent destinations cover over 150 countries/regions.

More than 20,000 customers from

North and South American, Europe, Middle East, East-South Asia, Africa, Australia, etc.







Accept different shipping terms, such as EXW, FOB, CFR, CIF, DDU and DDP, plenty of shipping resources are available to make you rest-assured of shipping.



Production process drawing

















PRODUCTION PROCESS DIAGRAM

生产工艺示意图





LED SCREEN CONNECTION DIAGRAM





Camino de, La Montaña 112, Los Pastores, 53340 Naucalpan de Juárez, Méx.